

UZIN RESILIENT CARE

Ready to use resilient floor cleaner

MAIN APPLICATION FIELD:

- ▶ pH neutral, daily cleaning and maintenance of resilient floor coverings

PRODUCT BENEFITS/FEATURES:

- ▶ resilient floor covering
- ▶ LVT / LVP (Luxury Vinyl Tile / Plank)
- ▶ linoleum
- ▶ VCT (Vinyl Composition Tile)
- ▶ rubber floor covering
- ▶ natural and artificial stone
- ▶ interior residential (apartments, houses)
- ▶ interior commercial (offices, hospitals, schools, universities, libraries, stores, assisted living)



PRODUCT BENEFITS/FEATURES:

UZIN Resilient Care is a premium, streak-free cleaner. Great for everyday use.

- ▶ multipurpose / for any resilient floor covering, also for natural and artificial stone
- ▶ pH neutral – safe for all floors
- ▶ great for daily cleaning
- ▶ one step process
- ▶ leaves no residue



TECHNICAL DATA:

Packaging	plastic canister, plastic bottle
Pack size	5 litres, 0.75 litres
Shelf life	min. 24 months
Color, wet	green
Application temperature	16 - 24 °C
Working time	approx. 60 minutes*
Ready for foot traffic	dry to touch

*At 21 °C and 65% relative humidity.



APPLICATION:

1. Sweep or vacuum the floor.
2. Dilute UZIN Resilient Care 1 : 200 with water (50 ml : 10 litre).
3. Wipe the substrate with a moist microfiber mop, e.g. RZ Folding Holder and RZ Fine-fibre Mop.
4. Let the residual moisture dry, don't wipe again.

IMPORTANT NOTES:

- ▶ A shelf life of 24 months when stored in moderately cool conditions, in the original packaging. Protect from frost. Carefully and tightly reseal opened containers and use the contents quickly. Allow containers to come to room temperature before use.

PROTECTION OF THE WORKPLACE AND THE ENVIRONMENT:

Maintenance cleaning agent, solvent-based without skin-absorbing substances. Not flammable. Use of barrier cream and good ventilation of the work area during use are recommended. Observe safety information on product label as well as safety data sheet.

DISPOSAL:

Where possible, collect product residues and re-use. Do not allow dispersal into drains, sewers or ground. Empty, scraped and drip-free containers are recyclable. Containers with liquid residue, as well as the liquid product, are classed as Special Waste. Dried product residues are classed as Construction Waste.